

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 September 2005 (29.09.2005)

PCT

(10) International Publication Number  
**WO 2005/090738 A1**

(51) International Patent Classification<sup>7</sup>: **E21B 21/01**,  
21/00, 4/00

(21) International Application Number:  
PCT/IT2005/000120

(22) International Filing Date: 4 March 2005 (04.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PD 2004 U 000027 19 March 2004 (19.03.2004) IT

(71) Applicant (for all designated States except US): **COMAC-  
CHIO S.R.L.** [IT/IT]; Via Callalta, 24/B, I-31039 Riese  
Pio X (TV) (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **COMACCHIO**,


**Pasqualino** [IT/IT]; c/o Comacchio S.r.l., Via Callalta,  
24/B, I-31039 Riese Pio X (TV) (IT). **COMACCHIO**,  
**Patrizio** [IT/IT]; c/o Comacchio S.r.l., Via Callalta, 24/B,  
I-31039 Riese Pio X (TV) (IT). **COMACCHIO**, **Renzo**  
[IT/IT]; c/o Comacchio S.r.l., Via Callalta, 24/B, I-31039  
Riese Pio X (TV) (IT).

(74) Agent: **BENETTIN, Maurizio**; Via Sorio, 116, I-35141  
Padova (IT).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.

[Continued on next page]

(54) Title: DRILLING HEAD WITH PROTECTIVE SCREEN



(57) Abstract: A drill head for drilling machines having a protective screen (S) for conveying the drilling mud discharged from the drivers (T1, T2) of the sleeves and drill rods (A), wherein said screen (S) reduces the mud fallout area in the vicinity of the drilling zone. The screen panel (S) has a generically U-shaped cross section, or in any case such a cross section as to cover wholly or partly at least three sides around the area where the mud is discharged from the drivers (T1, T2) of the rod (A) and sleeve (C). The screen panel (S) is joined to the structure of the drill head by means of connection supports (P) and translation mechanisms (Pa), in such a way as to translate said screen panel (S) parallel to the rod (A) and the sleeve (C).

WO 2005/090738 A1



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GI, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*